

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2016

Revision: 14.07.2016

1 Identification of the substance/mixture and of the company/undertaking

- Product identifier
- Trade name: LED Hardwax Oil Colors
- Article number: 04.LD11XXXX.XX
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance / the mixture Wood preservatives
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
- Wasziederij "De Vesting B.V."

Trasweg 12

NL-5712 BB Someren-Eind

The Netherlands

Tel: +31 493 496760

Fax: +31 493 493670

Email: vesting@euronet.nl

Web: www.vesting.nl

- Further information obtainable from: Product safety department.
- Emergency telephone number: During normal opening times: +31 493 496 760

2 Hazards identification

- Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1

H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Page 2/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2016

Revision: 14.07.2016

(Contd. of page 1)

Trade name: LED Hardwax Oil Colors

Hazard pictograms



Signal word Danger

· Hazard-determining components of labelling:

oxybis(methyl-2,1-ethanediyl) diacrylate

Glycerol, propoxylated, ester with acrylic acid

diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eve damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection. P273

Avoid release to the environment.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. P310

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

VOC (EC) 0 g/l (VOC-max. = 500 g/l (2010 A/i))

Restricted to professional users.

Keep out of the reach of children

Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous compon	ents:	
CAS: 57472-68-1	oxybis(methyl-2,1-ethanediyl) diacrylate	10-25%
EINECS: 260-754-3	♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317	
	polyetherpolyol acrylic ester	10-25%
	♦ Aquatic Chronic 2, H411	
CAS: 52408-84-1	Glycerol, propoxylated, ester with acrylic acid	2.5-10%
NLP: 500-114-5	♦ Eye Irrit. 2, H319; Skin Sens. 1, H317	
	Melanine acrylate	2.5-10%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 75980-60-8	diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide	≤ 2.5%
EINECS: 278-355-8		

Page 3/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2016 Revision: 14.07.2016

Trade name: LED Hardwax Oil Colors

(Con	td. of page 2)
Benzene, ethenyl-,copolymer with 2,5-Furandione and Benzene,1,1'-(1,1-dimethyl-3-methylene-1,3- propanediyl)bis-, rp. with Oxirane,	≤ 2.5%
♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Consult doctor in case of irritation.

Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Consult a doctor.

After swallowing:

Rinse out mouth.

Do not induce vomiting; call for medical help immediately.

Information for doctor:

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

Extinguishing media

Suitable extinguishing agents:

Water haze

Carbon dioxide

Sand

Fire-extinguishing powder

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- · Advice for firefighters
- Protective equipment:

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

· Environmental precautions:

Do not allow to penetrate the ground/soil.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Page 4/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2016 Revision: 14.07.2016

Trade name: LED Hardwax Oil Colors

(Contd. of page 3)

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Avoid contact with skin and eyes.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in a cool place.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

(Contd. on page

Page 5/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2016 Revision: 14.07.2016

Trade name: LED Hardwax Oil Colors

(Contd. of page 4)

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and	chemical properties
General Information	
Appearance:	The 14
Form: Colour:	Fluid Different according to colouring
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	>100 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	240 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1.08 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic at 20 °C:	100 mPas
Kinematic:	Not determined.

(Contd. on page 6)

Page 6/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2016 Revision: 14.07.2016

Trade name: LED Hardwax Oil Colors

(Contd. of page 5)

Other information

No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

75980-60-8 diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide

Oral | LD50 | >5000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation
- Causes serious eye damage.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.

 STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

· Aquatic toxicity:

75980-60-8 diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide

EC50/48 h 3.53 mg/l (daphnia magna)

EC50/72 h >2.01 mg/l (algea (pseudokirchneriella subcapitata))

LC50/96 h 1 - 10 mg/l (fish (danio rerio))

- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish

(Contd. on page 7)

GB-

Page 7/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2016 Revision: 14.07.2016

Trade name: LED Hardwax Oil Colors

(Contd. of page 6)

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· UN-Number · ADR, ADN, IMDG, IATA	not regulated	
	not regulated	
· UN proper shipping name · ADR, ADN, IMDG, IATA	not regulated	
· Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
· ADR, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
· Stowage Category	A	
Transport in bulk according to Annex I	I of Marpol	
and the IBC Code	Not applicable.	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information provided in these documents are based on our current knowledge of this product and be in good faith and to the best of our knowledge. However, this information shall explicitly not as technical (Contd. on page 8)

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.11.2016 Revision: 14.07.2016

Trade name: LED Hardwax Oil Colors

(Contd. of page 7)

specification and do not constitute a guarantee of the properties. We do not accept any liability for damage or consequences of any kind or size, either express or implied, arising from the use of this data could result. Existing laws, rules and regulations by the receiver and user of the product be met on their own responsibility. They should also ensure that the product for the intended application and use.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eve irritation.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

- Department issuing SDS: Product safety department.
- Contact: Laboratory
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS; Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PRT: Persistent Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3